



Municipal Sewage Sludge to Biodiesel as a Promising Renewable Fuel for the Future of Energy

Behnam Hatami¹, Samaneh Sedighi Khavidak^{2}*

¹ *Environmental Science and Technology Research Center, Department of Environmental Health Engineering, School of Public Health, Shahid Sadoughi University of Medical Sciences, Yazd, Iran.*

² *Department of Biology, Khoramabad Branch, Islamic Azad University, Khoramabad, Iran.*

ARTICLE INFO

LETTER TO EDITOR

Article History:

Received: 10 August 2018

Accepted: 20 November 2018

***Corresponding Author:**

Samaneh Sedighi Khavidak

Email:

sedighi.samaneh@yahoo.com

Tel:

+98 9133584815

Citation: Hatami B, Sedighi Khavidak S. **Municipal Sewage Sludge to Biodiesel as a Promising Renewable Fuel for the Future of Energy.** *J Environ Health Sustain Dev.* 2018; 3(4): 616-7.

Due to the global energy crisis caused by the rapid urbanization and industrialization along with a steady increase in energy demand, non-renewable energy sources are becoming increasingly scarce, and petroleum prices are rising. It is expected that the consumption of liquid fuels in the world increases from 87 million barrels per day in 2010 to 122 million barrels per day in 2040¹. On the other hand, the environmental considerations of fossil fuels such as air pollutants and excessive emission of greenhouse gases has increased concerns on environmental pollution. Utilizing clean renewable fuel is one convenient way to overcome both problems simultaneously.

In recent years, biodiesel as a renewable and environmentally friendly energy has been introduced to replace conventional fossil fuels. Biodiesel is biodegradable and non-toxic which compared to diesel has three technical (more fluidity, decrease the sediment in the fuel tank), environmental (absence of sulfur and aromatic

compounds, fewer emissions of hydrocarbons, CO, particulate matter) and economical (more energy intensity, fuel import costs) advantages. Over the past decade, biodiesel production in the United States increased from 700 to 2,890 million gallons per year.

Chemically, biodiesel is the result of a transesterification reaction of vegetable oils or animal fats with alcohol in the presence of a catalyst. The final product is a mixture of methyl esters of fatty acids (FAME). A variety of base, acid, enzyme and solid catalysts are used for this purpose. More than 80% of biodiesel production costs are related to the feedstock or raw material. Therefore, technical and economical selection of catalyst and feedstock can lead to cost-effective biodiesel production. So far, many studies have been conducted on biodiesel production from wide ranges of edible and non-edible oils such as sunflower oil², sesame oil³, rice bran oil⁴, Palm oil⁵, soybean oil⁶, rapeseed oil⁷ etc., animal fats

such as poultry fat ⁸, pork lard ⁹ etc. and microalgae ¹⁰. These resources are more valuable than being used to generate energy.

Municipal sewage sludge rich in lipids appears recently as an attractive non-food feedstock for biodiesel production in the future. The lipid of sludge contains specific amounts of triglycerides, phospholipids and fatty acids in the range of C10 to C18. Along with microorganisms are excellent resources. Microorganisms use the organic compounds of sewage to grow and store it as a lipid in their cellular bodies. Therefore, different conditions of microbial growth in a wastewater treatment system can lead to the production of different lipid contents. The amount of lipid in the primary sludge is about 7-35% (base on the dry weight), while this value is about 5-8% (base on the dry weight) for secondary sludge ¹¹.

In Iran, approximately 2.8 million tons of sewage sludge (base on the dry weight) is produced annually by wastewater treatment facilities. This amount is expected to increase as a result of urbanization and economic development. Incorrect management of this waste and incineration or disposal in land led to severe environmental challenges.

Therefore, considering that Iran is among the ten most energy-consuming countries, researches into biodiesel production from sewage sludge should be intensified.

This is an Open Access article distributed in accordance with the terms of the Creative Commons Attribution (CC BY 4.0) license, which permits others to distribute, remix, adapt and build upon this work, for commercial use.

References

1. Cea M, Sangaletti-Gerhard N, Acuña P, et al. Screening transesterifiable lipid accumulating bacteria from sewage sludge for biodiesel production. *Biotechnol Rep.* 2015; 8: 116-23.
2. Rakopoulos C, Antonopoulos K, Rakopoulos D, et al. Comparative performance and emissions study of a direct injection diesel engine using

blends of diesel fuel with vegetable oils or biodiesels of various origins. *Energy Convers Manag.* 2006; 47(18-19): 3272-87.

3. Saydut A, Duz MZ, Kaya C, et al. Transesterified sesame (*Sesamum indicum* L.) seed oil as a biodiesel fuel. *Bioresour Technol.* 2008; 99(14): 6656-60.
4. Sinha S, Agarwal AK, Garg SJEc, et al. Biodiesel development from rice bran oil: Transesterification process optimization and fuel characterization. *Energy Convers Manag.* 2008; 49(5): 1248-57.
5. Bo X, Guomin X, Lingfeng C, et al. Transesterification of palm oil with methanol to biodiesel over a KF/Al₂O₃ heterogeneous base catalyst. *Energy Fuels.* 2007; 21(6): 3109-12.
6. Tao G, Hua Z, Gao Z, et al. Synthesis and catalytic activity of mesostructured KF/Ca x Al₂ O (x⁺³) for the transesterification reaction to produce biodiesel. *RSC Adv.* 2012; 2(32): 12337-45.
7. Hajek M, Skopal F, Capek L, et al. Ethanolysis of rapeseed oil by KOH as homogeneous and as heterogeneous catalyst supported on alumina and CaO. *Energy.* 2012; 48(1): 392-7.
8. Shi W, Li J, He B, et al. Biodiesel production from waste chicken fat with low free fatty acids by an integrated catalytic process of composite membrane and sodium methoxide. *Bioresour Technol.* 2013; 139: 316-22.
9. Dias JM, Alvim-Ferraz MC, Almeida MFJBt. Production of biodiesel from acid waste lard. *Bioresour Technol.* 2009; 100(24): 6355-61.
10. Malakootian M, Hatami B, Dowlatshahi S, et al. Optimization of culture media for lipid production by *Nannochloropsis oculata* for Biodiesel production. *Environmental Health Engineering and Management Journal.* 2015; 2(3): 141-7.
11. Sangaletti-Gerhard N, Cea M, Risco V, et al. In situ biodiesel production from greasy sewage sludge using acid and enzymatic catalysts. *Bioresour Technol.* 2015; 179: 63-70.